




the top right corner of the screen





天服各署



* QIHANG 2.4G


944 BIS





Tap "+" and select " Compatible Pairing Mode" on APP.Select Wi-Fi SSID with ITEAD.**** and enter the password 1234578, and thengo back to eWeLink APP and tap "Next". Be patient

Pairing with RM2.4G remote control



1 Open the added device and click the settings icon in the upper right corner.








eWeLink Remote







Add Device





輸出电压 AC 100-240V 50/60Hz

外壳材料 PC V0

产品规格 42*42*20mm


支持平台 (Android 4.1 & iOS 9.0)或者更高版本

通信频率 WiFi(802.11 b/g/n 2.4GHz)

Material PC

Dimension 42*42*20mm





▲ S1/S2接或不接机械开关两端,设备都可以正 常使用。为确保安全,请勿接入零火线等强电。

使用该设备前请检查以下事项

● 手机必须能够访问APP商店并下载APP:

如果您的无线路由器设置了Mac地址过滤。

请先进入路由器后台关闭Mac过滤功能。

10.0以上版本;

● 您的智能手机已链接上一个能上网的2.4G

● 手机系统版本需要是安卓5.0以上,或者IOS

设备与易微联APP的配对方法

1 下载易微联APP

王线認由與

Ω

- 季机连接2.4GHz的WiFi,打开手机蓝牙;
- 3 长按配对按键5秒以上,指示灯快闪两 次,长亮一次,进入配网模式。
- 4 打开APP,点击右上角 ↔ ,选择 "添加设备"



5 选择手机连接的2.4GHz-WiFi, 确 认相关信息无误,点击"下一步";



6 搜索到可添加的设备后,点击右边 的 🕀 进行添加。



兼容模式(AP)

如果使用快速添加模式配网失败,请使用"兼容 模式(AP)"进行配对。

- 1 长按配对按键5秒直到设备指示灯呈"两短 一长闪烁"状态,松开按键。再次长按配对 按键5秒直到设备指示灯呈"快闪"状态,此 时设备讲入兼容模式。
- 在app界面,点击"+",选择"兼容模式"。先 把移动设备连接上Wi-Fi账号为:ITEAD-*****,密码为:12345678,然后回到"易微 联"app,点击"下一步",等待配对完成。

设备与RM2.4G遥控器配对







设备设置 局域网控制 设备设置 轻智能情景 轻智能遥控器 操作通知 操作记录

2 选择"轻智能遥控器"。

网络指示灯









注:如需删除RM2.4G遥控器,进入添加遥控器 界面,删除即可。

产品特点

本设备是一款WiFi智能开关。用您的智能手机在 任何地方打开或关闭家里的设备,设置定时开/关, 分享给您的家人控制等等。







APP控制 智能定时 情景联动 语音控制 上电设置